

N175

1.75" COMMERCIAL POLYURETHANE INSULATED STEEL DOOR



Overview:

- Polyurethane insulation is zero-ozone depleting and provides higher thermal properties which result in significant energy savings.
- Cavity-free, uniform insulation ensures excellent adhesion to the sheet metal resulting in an exceptional Strength to weight ratio that qualifies for a wide range of applications.
- Sections are evenly filled using a continuous process with CFC/HCFC-free polyurethane insulation.
- Insulated sections fabricated from pre-painted, hot dipped galvanized Steel sheets with rigid polyurethane insulation core, face sheet Stucco embossed and rib reinforced.
- Sections feature thermal break, Steel-polyurethane-Steel sandwich formed in a computer-controlled continuous process


NORTHLAND

GARAGE DOORS



www.northland-doors.com

Product Specifications



Section Details

SECTION THICKNESS

ST175: 1 3/4" (45mm)

THERMAL VALUE OF SECTIONS*

ST 175: R 16

FACE SHEET PROFILE Multi-Ribbed / Ribbed

EXTERIOR FACE SHEET THICKNESS

ST175: 0.019" (0.48mm)

MAXIMUM OPENING WIDTH**


ST150: 16'-2" (4826mm)

ST175: 36'-2" (11024mm)

MAXIMUM OPENING HEIGHT 22' (6706mm)

FINISH Two coat, baked-on paint system on exterior side, primer and polyester finish coat.
Available in White, Silver & Brown

Glazing Options



Warranty

10 years against delamination of the panels
1 year on materials and workmanship

*Thermal Values Calculated. **For larger sizes, please consult factory.

SECTION SCHEDULE

DOOR OPENING HEIGHT	Sections High	DOOR OPENING WIDTH	Max no. of Windows
7'-1" to 8'-1" (2159mm to 2464mm)	4	8'-0" to 9'-2" (2438mm to 2794mm)	2
8'-2" to 10'-1" (2489mm to 3073mm)	5	9'-3" to 12'-2" (2819mm to 3708mm)	3
10'-2" to 12'-1" (3099mm to 3683mm)	6	12'-3" to 16'-2" (3734mm to 4928mm)	4
12'-2" to 14'-1" (3708mm to 4293mm)	7	16'-3" to 19'-2" (4953mm to 5842mm)	5
14'-2" to 16'-1" (4318mm to 4902mm)	8	19'-3" to 24'-2" (5867mm to 7366mm)	6
16'-2" to 18'-1" (4928mm to 5512mm)	9	24'-3" to 28'-2" (7391mm to 8585mm)	7