

SPIRAL®

High Security, High Speed and Architectural Style - All in One Door

The Spiral® rigid rolling door offers high-speed operation for high-traffic situations and rigid aluminum slat construction that provides durability and security. The exclusive, patented Spiral design guards against wear and tear on the aluminum panel, resulting in minimal maintenance, preserved aesthetics and longer life. Crisp lines give the Spiral door a stylish look that seamlessly integrates into any architectural design.

The Spiral door is ideal for securing parking, commercial, automotive retail, government, institutional and industrial applications. Because its anodized aluminum slats will not corrode, you can count on its look to last for many years even under the worst weather conditions.

Spiral high performance is guaranteed with a **5-year limited warranty**.





Solid Security

- Minimum 1 3/16-inch thick double-walled aluminum slats
- Integral rubber weatherseal
- Continuous heavy-duty hinge system

High Speed

 Opening speed of up to 60 inches per second improves traffic flow in fast-paced environments

Ultra Quiet

• Spiral track design features no metal-to-metal contact for remarkably quiet operation

Unparalleled Performance

 Variable speed AC drive system - with soft acceleration and deceleration - smooths out routine stops and starts

Energy Efficient and Tight Seal

 Aluminum slats and durable rubber membrane provide a 100% seal against dust, drafts and inclement weather

QUALITY. PERFORMANCE. RELIABILITY.



HIGH PERFORMANCE RIGID ROLLING DOOR



Automotive Dealership





Parking



Security





Size/Dimensions

- Maximum width up to 26'3"
- Maximum height up to 22'11"

Travel Speed

Opening speed up to 60 inches per second

Spiral Technology

- Unique, patented design creates no metal-to-metal contact, resulting in less wear and tear on the panel
- Ultra quiet and low maintenance operation
- Utilizes AC drive motor with variable speeds to allow for soft acceleration and deceleration



AC drive motor

Architectural Styling

- Sleek, double-walled, clear anodized aluminum slats are 6 inches high with an integral weatherseal between each panel
- Durable 'Rytec silver' powder coated finish* is UV-stable and resists rust, corrosion and fingerprints



Six-inch high slats shown

Electrical Controls

- System 4[®] controller housed in a NEMA 4X rated enclosure with factory set parameters
- Intelligent processor monitors and controls power consumption during operation
- Advanced self-diagnostics for troubleshooting

optional rotary disconnect



System 4 shown with

Panel Design


- Integral rubber weatherseal between the slats provides a tight weatherseal across the entire panel
- Patented hinge design allows for removal and replacement of individual slats without disassembling the door panel



Integral rubber weatherseal

Safety is Standard

- SmartSurround® Advanced **Detection and Alert System** Intuitive light curtain system + LED safety lights for traffic recognition, detection and alerting
- Advanced³ Light Curtain Safety System continuously monitors doorway opening
- Mechanical brake release lever allows door opening in the event of power failure



SmartSurround® light curtains and LED light strips provide 4-corner

Warranty

- Five-year limited warranty on motor/mechanical components and materials
- Two-year limited warranty on electrical components

Options

- Pre-wired premium package
- Insulated, ventilated or vision slats
- Hood and motor covers
- Compact BTA4 remote door controller
- Electric reversing edge with Ry-Wi® Wireless System
- Powder coated finish also available in RAL classic colors or custom match
- Multiple door activation options available; contact factory for details



Optional vision slats shown

*Side columns and head console; excludes some US/R models.













